

# Nexus FS Point-Of-Use



GNB 215i-SIP



GNW 215i-SIP

## Features

- Stylish and contemporary design
- Elevated dispensing height and larger dispensing area
- Built-in cup dispenser (holds 3" diameter cups)
- Hot & cold temperature indicator
- Safety lock function for hot & cold water
- Fast flow electronic dispensing
- Accu-Temp - Serves water at the proper temperature every time
- Stay-Cool - Keeps the residual water in the cold waterway chilled and ready to serve
- SIP enhanced sanitization sanitizes cold reservoir, waterways and spout
- i-Boil - Increases the hot water temperature to just under boiling - perfect for coffee, teas, noodles, etc.
- Dual mechanical float for reliability
- Room for filter inside
- Available in black or white
- UL certified



Models

H&C: GNB 215i-SIP, GNW 215i-SIP

# Nexus FS

## Power

Voltage (V)	115, 220, 100
Frequency (Hz)	50/60
Power Consumption	5.42A / 602W / 220V
Cold Power Consumption	1.44A / 118W / 220V
Hot Power Consumption	4.33A / 500W / 220V
ES (KWH/24hrs)	0.665
% lower than ES Standard	45%

## Hot Water System

Avg. Hot Water Temp at nozzle @ 24°C ambient(Before/After On)	79.6°C / 84.96°C
Hot water ARI Rating	45 178ml > 74°C +/- 10%
Hot Thermostat / Heat Limiter	95°C +/-3°C
Hot Thermostat / Thermister Cycle	78° - 88°C
i-Boil Set Point	89°C
Avg. Temp of i-Boil at nozzle @ 24°C ambient (After On)	94.9°C
Hot Water Flow Rate	42ml/sec
Hot Water Flow Rate (ml per sec)w/Accu-Temp delay	37.5 ml/sec
Hot Tank Size (L)	1.2L
Heat Band Wattage	520W

## Cold Water System

Avg. Cold Water Temp at nozzle @ 24°C ambient(Before/After ON)	6.63°C / 5.18°C
Cold Water ARI Rating	27 147ml < 10°C +/-10%
Cold Thermostat Set Point	7°C +2°/-4°C
Cold Water Flow Rate	45 ml/sec
Cold Water Flow Rate (ml per sec)w/ Accu-Temp delay	40.5 ml/sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (L)	3.78 / 2.84 / 1.5 L

## Weights and Measurements

Net Weight (Kg)	13.48
Gross Weight (Kg)	14.98
Cooler Dimensions / Boxed Dimensions WxDxH (cm)	29.6x38x110.5 / 32x35.5x113
Container Load (20')	224
Container Load (40')	456
Container Load (40' HC)	456
Container Load (45' HC)	532
Certifications	UL