

# ***GLACIER***

*Bottled Water Cooler*



  
**Crystal Mountain™**

# GLACIER

## *Bottled Water Cooler*

The Glacier cooler is sophistication simplified. The rounded cabinet has a stylish fluted front, giving it a classic Greek column design. Features include approved food grade HDPE removable reservoir and the sealed Crystal Guard non-spill system. The Glacier is available in white, black or granite with an optional bottle cover and if desired, the DryGuard™ system can be fitted at the factory.



Child-proof hot water faucet



Cup dispenser



Hot water ON and OFF switch



Removable drip tray

## **DryGuard™**

Crystal Mountain's patented sealed-system DryGuard™ feature, molded from polypropylene, protects floors against leaks caused by cracked and faulty bottles.





# GLACIER

*Bottled Water Cooler*

## Performance & Specifications

### General

Air cooled, bottled type water cooler provided with a power supply cord for connection to source of power supply

### Cooler Cabinet

Blow molded, high density polyethylene(HDPE) resistant to cracking  
Other colours are also available when order by container

### Faucet Type

Concealed faucet for optimum hygiene  
Constructed of FDA approved nylon and silicon tubing  
Optional child lock safety function

### Cold Water Tank Specifications

Stainless steel #304 or HDPE casing with 2.0L (0.5 gal) volume  
Cold water cooling capacity of 3.5L (0.9 gal)/hour based on 21°C (69.8°F) room temperature

### Cold Water Thermostat

Preset at factory to dispense water at temperature from 2-10°C (35.6-50°F)  
Adjustable cold control located at the back of the cabinet

### Hot Water Tank Specifications

Stainless steel #304 casing with 1.8L (0.5 gal) volume  
Hot water capacity of 4.5L (1.2 gal)/hour based on 21°C (69.8°F) room temperature

### Hot Water Thermostats and Heater

Automatic thermostat control with temperature range of 75-92° C (167-197.6°F)  
Manual thermostat reset in case of automatic thermostat failure  
450W external heater band  
ON/OFF switch located at the back of the cabinet  
Electronic Thermostat System (ETS) is available, which provides for a temperature control range of 88-92°C (190.4-197°F)

### Compressor Type

Hermetically sealed reciprocating compressor  
(220-240VAC 50Hz) (110-115VAC 60Hz)

**Refrigerant Type:** R134a (CFC Free)

**Refrigerant Charge:** 28.4g (1.0 oz)

### Dimensions & Freight Data

#### Product Dimensions

314mm deep x 312mm wide x 980mm high  
(12.4" deep x 12.2" wide x 38.6" high)

**Product Weight:** H&C:14.7kg (32.4 lb) C&C:13.8kg (30.5 lb)

#### Product Boxed Dimensions

320mm deep x 330mm wide x 1000mm high  
(12.6" deep x 12.4" wide x 38.6" high)

**Product Boxed Weight:** H&C:15.8kg (34.8 lb) C&C:15.1kg (33.3 lb)

**20FT Container Quantity:** 252 Units

**40FT Container Quantity:** 518 Units



*All performances are tested in a controlled environment, certified by a third party. To learn more about these standards, please speak to your Crystal Mountain representative.*





# GLACIER



Website: [www.crystalcoolers.com](http://www.crystalcoolers.com)

## Crystal Mountain Products Limited

### North American Sales Office

11925 -145<sup>th</sup> Street  
Edmonton, Alberta  
Canada T5L 2H4  
Tel: 1 800 878 6422  
Tel: 1 780 454 4545  
Fax: 1 780 454 9816  
E-mail: [cmcanada@crystalcoolers.com](mailto:cmcanada@crystalcoolers.com)

### European Sales Office

Fence House, Fence Avenue  
Macclesfield, Cheshire  
United Kingdom SK10 1LT  
Tel: +44(0) 1625 439 111  
Fax: +44 (0) 1625 502 527  
E-mail: [cmeurope@crystalcoolers.com](mailto:cmeurope@crystalcoolers.com)

## Crystal Mountain International Limited

### Hong Kong Sales Office

Room 610, Winfield Commercial Building  
6-8a Prat Avenue, Tsimshatsui  
Kowloon, Hong Kong  
Tel: (852) 2368 1989  
Fax: (852) 3017 6727  
E-mail: [cmasia@crystalcoolers.com](mailto:cmasia@crystalcoolers.com)

CE cUL US LISTED CB CCC SASO ISO9001 WEEE RoHS



*Crystal Mountain has a policy of continuous development and reserves the right to change specifications without notification.*

GLB REV0410