



Top Wave Bottled Water Cooler

Cook & Cold
VB 110 (Black)
VW 110 (White)

Hot & Cold
VB 210 (Black)
VW 210 (White)



Features

- 2.0L / .53G stainless steel hot tank
- 3.78L / 1G stainless steel cold tank
- High quality, high output refrigeration and heating system
- Water is dispensed through industry standard Tomlinson style faucets that allow for Hot and Cold or Cook and Cold options
- Solid one-piece cabinet made from High Density Polyurethane that is extremely durable and easy to clean
- Removable, one-piece drip tray for easy cleaning
- Cup dispenser (optional)
- Available in black and white
- Available in Hot & Cold or Cook & Cold
- NoLeak® EZ-Fill®
- Energy Star rated hot tank with On/Off switch
- UL listed



Bottled Water Cooler

Power

115, 220, 110
50/60
4.89A / 554W / 115V
1.42A / 118W 115V
3.87A / 449W / 115V
0.81
7%

Hot Water System

Avg. Hot Water Temp at Nozzle @ 77°F Ambient (Cut-in / Cut-out Temp)	175.6°F 184.1°F +/- 4°F
Hot Water ARI Rating	45, 6 oz. > 165°F +/- 10%
Hot Thermometer / Heat Limiter	203°F +3 /- 8°F
Hot Thermostat / Thermistor Cycle	167°F +/- 11°F / 187°F +/- 4°F
Hot Water Flow Rate	0.78 - 0.87 oz./sec
Hot Tank Size (Liter : Gallon)	2.0L : 0.53G
Heat Band Wattage	450W

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F Ambient (Cut-in / Cut-out Temp)	45.87°F / 42.2°F
Cold Water ARI Rating	27, 5 oz. > 50°F +/- 10%
Cold Thermostat Set Point	45°F + 3°F/-8°F
Cold Water Flow Rate	1.1-1.4 oz/sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter : Gallon)	3.78 / 2.08 / 1.51 : 1 / 0.55 / 0.4

Weights and Measurements

Net Weight (H&C / C&C Lbs.)	26.5 / 24.3
Gross Weight (H&C / C&C Lbs.)	29.5 / 27.3
Max Distance from Drip Tray to Faucet (Inch : mm)	7.8" : 198mm
Faucet / Dispense Height (Inch : mm)	27.8 : 705mm
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12.5x13.4x38.4/ 13x13.6x38.78
Container Load (20')	224
Container Load (40')	476
Container Load (40' HC)	476
Container Load (45' HC)	532
Certifications	UL Listed
Models (Filtration)	VB110, VW110, VB210, VW210

Warranty:

3 years: Sealed refrigeration system
2 years: Parts (electrical to include cold controls, relay overloads and PCB's)

Phone: (647) 381-8990
email: demmons@applitechcanada.com
web: applitechproducts.com/